

Safety Data Sheet

Hexane

SECTION I - IDENTIFICATION



DATE PREPARED: 9/23/1994
REVISION DATE: 4/6/2011
CHEMTEL: 800-255-3924
PRODUCT CODE: HEX

ADDRESS: 2141 Palomar Airport Rd. Suite 125
Carlsbad, CA 92011

EMERGENCY PHONE NUMBER: (800) 255-3924

PRODUCT NAME: Hexane

CHEMICAL FAMILY:

CAS NUMBER: 110-54-3

SECTION II - HAZARDOUS IDENTIFICATION


GHS CLASSIFICATION:

Classification

Flammable Liquids	Category 2
Aspiration Hazard	Category 1
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Specific target organ toxicity, single exposure, N	Category 3
Reproductive Toxicity	Category 2
Specific target organ toxicity, repeated exposure	Category 2
Hazardous to the aquatic environment, acute hazard	Category 2
Hazardous to the aquatic environment, long-term hazard	Category 2

DANGER!

GHS LABEL:



Hazard Statements

H225	Highly flammable gas and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause dizziness or drowsiness
H361	Suspected of damaging fertility or the unborn child
H373	Causes damage to organs through prolonged or repeated exposure

Safety Data Sheet

Hexane

- H401 Toxic to aquatic life
H411 Toxic to aquatic life with long lasting effects

Precautionary Statements

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surface - No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/light/equipment, etc.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P281 Use personal protective equipment as required.
- P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P302+352 IF ON SKIN: Wash with soap and water.
- P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.
- P308+313 IF exposed or concerned: get medical advice/attention.
- P312 Call a POISON CENTER or a doctor/physician if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P331 Do NOT induce vomiting.
- P332+313 If skin irritation occurs: get medical advice/attention.
- P337+313 If eye irritation persists get medical advice/attention.
- P362 Take off contaminated clothing and wash before reuse.

Safety Data Sheet

Hexane

P370+378	In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction.
P391	Collect spillage.
P403+233	Store in a well ventilated place. Keep container tightly closed.
P403+235	Store in a well ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to an approved waste disposal plant.

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS #	Component%	OSHA PEL	ACGIH TLV
Hexane	110-54-3	100%	50 ppm	50 ppm

SECTION IV - FIRST AID MEASURES

Contact with eyes: Flush with water for 15 minutes. Seek immediate medical attention.

Skin contact: Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, seek immediate medical attention.

Inhalation: Remove victim to fresh air. Administer oxygen or artificial respiration if breathing is affected or stopped. Seek immediate medical attention.

Ingestion: If swallowed. Do not induce vomiting. Seek immediate medical attention.

SECTION V - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Water fog, foam, CO₂, dry chemical.

Special Fire Fighting Procedures Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling.

Unusual Fire Fighting Hazards: Product is flammable and may be ignited by heat, sparks, flames or other sources of ignition (e.g., static electricity, pilot lights or mechanical/electrical equipment). Vapors are heavier than air and may accumulate in low areas. Vapors may travel considerable distances to a source of ignition where they can ignite, flashback or explode. May create vapor/air explosion hazard indoors, outdoors or in sewers. If container is not properly cooled, it can explode in the heat of a fire.

Safety Data Sheet

Hexane

SECTION VI - ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Keep all sources of ignition and hot metal surfaces away from spill or release.
Evacuate all unprotected personnel from the area.
Product in liquid and vapor form is extremely flammable.
- Environmental Precautions:** Prevent liquid from entering drains, sewers or waterways.
Contain spill if it can be done with minimal risk.
Notify proper authorities. Reportable Quantity is 9090 pounds or 1620 gallons.
- Methods for Cleaning Up:** Use foam on spills to minimize vapors.
Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container.

SECTION VII - HANDLING AND STORAGE

- Handling and Storage:**
- NFPA Class I storage.
 - Vent container carefully before opening.
 - Bond and ground all equipment when transferring from one vessel to another. The use of explosion-proof equipment is recommended.
 - "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources.
 - Keep containers tightly closed when not in use.
 - Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

Component Name	CAS #	OSHA PEL	ACGIH TLV
Hexane	110-54-3	50 ppm	50 ppm

Engineering Controls: Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV.

Monitoring: Follow accepted work practices for handling a flammable material.
Do not eat, drink or smoke in areas where this chemical is used or stored.
Have eye wash stations and safety showers readily available.

Personal Protective Equipment (PPE)

Eye Protection: Goggles or approved OSHA device with side shields; do not wear contact lenses when handling this product.

Skin Protection: Impervious solvent resistant gloves.
Impervious apron and work boots recommend where splashing may occur.

Safety Data Sheet

Hexane

Respiratory Protection: Use the proper respirator in areas where the chemical exposure is unknown or above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear, Colorless Liquid
Odor	Characteristic hydrocarbon odor
pH@25°C	-
Melting/Freezing Point	-
Boiling Point	145-165°F
Flashpoint	-20°F, TCC
Specific Gravity	0.674
Solubility	Negligible
Auto-Ignition Temperature	-
Decomposition Temperature	-
VOC Content	100% (5.6#/gal)
Odor Threshold	-
Boiling Range	145-165°F
Evaporation Point	>6 (Butyl Acetate=1)
Flammable Limits - Upper	8%
Flammable Limits - Lower	1%
Vapor Pressure	140 mmHg @20°C
Vapor Density (Air=1)	3 (Air=1)
Viscosity	-

SECTION X - STABILITY AND REACTIVITY

Stability: Stable, under normal conditions of storage and handling.

Conditions to Avoid: Extreme heat and ignition sources.

Hazardous Decomposition/Byproducts: CO, CO₂, and noxious smoke under extreme fire conditions

Hazardous Polymerization: Will not occur.

Polymerization Conditions to Avoid: None

Safety Data Sheet

Hexane

SECTION XI - TOXICOLOGICAL INFORMATION

Likely Route of Exposure: Contact and inhalation; ingestion possible.

Inhalation: May cause irritation to the upper respiratory tract and CNS depression. Low to moderate degree of toxicity by inhalation.

Eye Contact: Causes eye irritation including stinging, watering and redness which may result in corneal injury.

Skin Contact: Contact may cause mild skin irritation including redness, burning and drying/cracking of the skin. No harmful effects from skin adsorption are expected.

Ingestion: Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia and edema.

Toxicity:

Component Name	LD50	LC50
Hexane	Oral - rat - 25,000 mg/kg; Dermal - rabbit - 2,001 mg/kg	Inhalation - rat - 4H/171.6 mg/l

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicity: Information not available.

Mobility: Information not available.

Degradability: Information not available.

BioAccumulation: Information not available.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert. Can be disposed of by controlled incineration. Excessive quantities should not be permitted to enter drains, sewers, or water courses. Empty containers should be air dried before disposing.

Safety Data Sheet

Hexane

SECTION XIV - TRANSPORT INFORMATION

DOT SHIPPING INFORMATION

Proper Shipping Name: Hexanes

Contains:

Hazard Class and Label: 3

Identification Number: UN 1208

Packaging Group: II

Label Required:

SECTION XV - REGULATORY INFORMATION

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Acute	Chronic	Fire	Pressure	Reactive
X		X		

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

Component Name	CAS #	% by wt.
Hexanes	110-54-3	100%

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

Component Name	CAS #	% by wt.	RQ (lbs.)
Hexane	110-54-3	100%	5,000

SECTION XVI - OTHER INFORMATION

HMIS Health: 2

HMIS Flammability: 3

HMIS Reactivity: 0

Additional:

Specification Information

Department issuing data sheet: Compliance

Email address: compliance@transcheminc.com

Training necessary: Follow all local, state and federal regulations

Intended Use of Product:

Seller and manufacturer disclaim any implied or expressed warranties, including warranties of merchantability or fitness of this product for any particular purpose. In no event shall seller be liable for any claim for incidental or consequential damages arising out of or in connection with the sale, delivery, transportation or use of this product. Seller's and manufacturer's liability in all events is limited to, and shall not exceed the purchase price paid for this product.