Iso-Butyl Acetate

## **SECTION I - IDENTIFICATION**



 DATE PREPARED:
 9/18/1990

 REVISION DATE:
 5/29/2014

 CHEMTEL:
 800-255-3924

 PRODUCT CODE:
 IBAC

Carlsbad, CA 92011

**EMERGENCY PHONE NUMBER: .....** (800) 255-3924

PRODUCT NAME: ..... Iso-Butyl Acetate

CHEMICAL FAMILY: .....

**CAS NUMBER:** ..... 110-19-0

## **SECTION II - HAZARDOUS IDENTIFICATION**

## **GHS CLASSIFICATION:**

## Classification

Flammable Liquids Category 2

## DANGER!

## **GHS LABEL:**



## **Hazard Statements**

H225 Highly flammable gas and vapor

# Iso-Butyl Acetate

## **Precautionary Statements**

P210 Keep away from heat/sparks/open flames/hot surface - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/light/equipment, etc.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P370+378 In case of fire: Usedry sand, dry chemical, or alcohol-resistant foam for extinction.

P403+235 Store in a well ventilated place. Keep cool.

P501 Dispose of contents/container to an approved waste disposal plant.

#### **SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS**

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS#	Component%	OSHA PEL	ACGIH TLV
Acetic Acid, 2-Methylpropyl Ester	110-19-0	100%	150 ppm	150 ppm

## **SECTION IV - FIRST AID MEASURES**

Contact with eyes: Flush with water for 15 minutes. Seek immediate medical attention.

**Skin contact:** Wash exposed areas with water and mild soap. Remove contaminated clothing

immediately and launder before reuse. If irritations persist, seek immediate

medical attention.

**Inhalation:** Remove victim to fresh air. Administer oxygen or artificial respiration if breathing is

affected or stopped. Seek immediate medical attention.

**Ingestion:** If swallowed. Do not induce vomiting. Seek immediate medical attetntion.

# **SECTION V - FIREFIGHTING MEASURES**

**Suitable Extinguishing Media:** Water fog, foam, CO2, dry chemical.

# Iso-Butyl Acetate

**Special Fire Fighting Procedures** Use self-contained breathing apparatus and full bunker gear in fire areas.

Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water  $\,$ 

used for cooling.

**Unusual Fire Fighting Hazards:** Product is flammable and may be ignited by heat, sparks, flames or other

sources of ignition (e.g., static electricity, pilot lights or mechanical/electrical equipment). Vapors are heavier than air and may accumulate in low areas. Vapors may travel considerable distances to a source of ignition where they can ignite, flashback or explode. May create vapor/air explosion hazard indoors, outdoors or in sewers. If container is not properly cooled,

it can explode in the heat of a fire.

#### **SECTION VI - ACCIDENTAL RELEASE MEASURES**

**Personal Precautions:** Keep all sources of ignition and hot metal surfaces away from spill or

release.

Evacuate all unprotected personnel from the area.

**Environmental Precautions:** Prevent liquid from entering drains, sewers or waterways.

Contain spill if it can be done with minimal risk.

Notify proper authorities.

**Methods for Cleaning Up:** Use foam on spills to minimize vapors.

Using only non-sparking tools and explosion proof equipment, collect

spill on absorbent material and put into approved container.

## **SECTION VII - HANDLING AND STORAGE**

## **Handling and Storage:**

- NFPA Class I storage.
- Vent container carefully before opening.
- Bond and ground all equipment when transferring from one vessel to another. The use of explosion-proof equipment is recommended.
- "Empty" containers retain residue and/or vapor and may be dangerous.
   Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources.
- Keep containers tightly closed when not in use.
- Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.

#### SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

#### **EXPOSURE LIMITS:**

Component Name	CAS#	OSHA PEL	ACGIH TLV
Acetic Acid, 2-Methylpropyl Ester	110-19-0	150 ppm	150 ppm

Engineering Controls: Adequate local or mechanical to reduce vapor or mist to below the PEL or

TLV.

Iso-Butyl Acetate

**Monitoring:** Follow accepted work practices for handling a flammable material.

Do not eat, drink or smoke in areas where this chemical is used or stored.

Have eye wash stations and safety showers readily available.

**Personal Protective Equipment (PPE)** 

**Eye Protection:** Goggles or approved OSHA device with side shields; do not wear contact

lenses when handling this product.

**Skin Protection:** Impervious solvent resistent gloves.

Impervious apron and work boots recommend where splashing may occur.

Respiratory Protection: Use the proper respirator in areas where the chemical exposure is

unknown or above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES				
Appearance	Clear Colorless Liquid			
Odor	Distinct Fruity Acetate Odor			
pH@25°C	-			
Melting/Freezing Point	-			
<b>Boiling Point</b>	234-246°F			
Flashpoint	66°F (18.9 °C); TCC			
Specific Gravity	0.872			
Soluability	Slight			
Auto-Ignition Temperature	-			
Decomposition Temperature	-			
VOC Content	100%			
Odor Threshold	-			
Boiling Range	234-246°F			
Evaporation Point	1.4 (Butyl Acetate=1)			
Flammable Limits - Upper	10.5%			
Flammable Limits - Lower	2.4%			
Vapor Pressure	12.5 mmHg @ 20°C			
Vapor Density (Air=1)	4.0(Air=1); Calculated			
Viscosity	-			

# **SECTION X - STABILITY AND REACTIVITY**

Stability: Stable

**Conditions to Avoid:** Extreme heat and ignition sources.

Hazardous Decomposition/Byproducts: CO, CO2, and noxious smoke under extreme fire conditions

Hazardous Polymerization: Will not occur.

# Iso-Butyl Acetate

**Polymerization Conditions to Avoid:** 

## **SECTION XI - TOXICOLOGICAL INFORMATION**

**Likely Route of Exposure:** Contact and inhalation; ingestion possible.

Inhalation: May cause irritation to the upper respiratory tract and CNS depression.

Low to moderate degree of toxicity by inhalation.

**Eye Contact:** Causes eye irritation including stinging, watering and redness which

may result in corneal injury.

**Skin Contact:** Contact may cause mild skin irritation including redness, burning and

drying/cracking of the skin.

Ingestion: Aspiration hazard. Can enter the lungs during swallowing or vomiting

and cause chemical pneumonia and edema.

Low degree of toxicity by ingestion.

**Toxicity:** 

Component Name	LD50	LC50	
Acetic Acid, 2-Methylpropyl Ester	Oral - rabbit - 4,763 mg/kg; Oral - rat - 13,400 mg/kg;	Not Established	

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

## **SECTION XII - ECOLOGICAL INFORMATION**

**Ecotoxicity:** Information not available.

Mobility: Information not available.

Degradability: Information not available.

**BioAccumulation:** Information not available.

#### **SECTION XIII - WASTE DISPOSAL CONSIDERATIONS**

Follow local and national regulations. Consult disposal expert. Can be disposed of by controlled incineration. Excessive quantities should not be permitted to enter drains, sewers, or water courses. Empty containers should be air dried before disposing.

Iso-Butyl Acetate

#### SECTION XIV - TRANSPORT INFORMATION

#### **DOT SHIPPING INFORMATION**

Proper Shipping Name: Isobutyl Acetate

Contains:

Hazard Class and Label: 3

Identification Number: UN 1213

Packaging Group:

Label Required:

# **SECTION XV - REGULATORY INFORMATION**

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

## SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

# SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Acute	Chronic	Fire	Pressure	Reactive
X		X		

#### **SARA TITLE III SECTION 313 SUPPLIER INFORMATION:**

No chemicals in this material are subject to the reporting requirements.

## **CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:**

Component Name	CAS#	% by wt.	RQ (lbs.)
Acetic Acid, 2-Methylpropyl ester	110-19-0	100%	5,000

## **SECTION XVI - OTHER INFORMATION**

 HMIS Health:
 2

 HMIS Flammability:
 3

 HMIS Reactivity:
 0

Additional:

**Specification Information** 

**Department issuing data sheet:** Compliance

Email address: compliance@transcheminc.com

**Training necessary:** Follow all local, state and federal regulations

## **Intended Use of Product:**

Seller and manufacturer disclaim any implied or expressed warranties, including warranties of merchantability or fitness of this product for any particular purpose. In no event shall seller be liable for any claim for incidental or consequential damages arising out of or in connection with the sale, delivery, transportation or use of this product. Seller's and manufacturer's liability in all events is limited to, and shall not exceed the purchase price paid for this product.